

# DataSheet

Market-leading Commander® has something new to offer – CommanderEDGE. BS EN3 Kitemark approved across the range, this range has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO<sub>2</sub> and Powder models and offers solutions for almost all situations. The internationally-recognised BS Kitemark is assurance of dependable design and manufacture.



## COMMANDEREDGE

**PRODUCT CODE**  
WS6E | WS9E

**PRODUCT GROUP**  
CommanderEDGE Extinguishers

**DIMENSIONS (mm)** (height x width x diameter)  
WS6E: 502 x 197x 160  
WS9E: 620 x 330 x 185

**WEIGHT**  
WS6E: 9.9kg  
WS9E: 14.2kg


- Kitemarked to BS EN3
- Manufactured in Europe\*
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Plastic base skirt for protection
- Polyethylene internal lining
- 35kVa Dielectric test certified


\*WS6E model only

## WATER FIRE EXTINGUISHERS

Water extinguishers still remain a popular choice for Class A fire risks. This model is Kitemarked and comes complete with a plastic base skirt for protection. Both models have passed the 35kVa Dielectric test and comply fully with BS EN3-7: 2004 Clause 9 - Dielectric test for water-based extinguishers. All CommanderEDGE extinguishers are screen printed and come with a 5-year warranty. Water – the economical, reliable choice for Class A fires.


Technical Specification	WS6E	WS9E
Capacity	6 litre	9 litre
Fire Rating	13A	13A
Extinguishing Medium	Demineralised water	Water
Working Pressure	15 bar at temp 20°C	14 bar
Temperature Range	+5°-+60°C	+5°-+60°C
Cylinder Material	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen

 029 2086 8333

 029 2085 0627

 sales@checkfire.co.uk

 www.CheckFire.co.uk



\*MPA Dresden applies to 6ltr unit only  
\*MED Approval applies to 9ltr unit only