

DataSheet

Market-leading Commander® has something new to offer – CommanderEDGE. BS EN3 Kitemark approved across the range, this range has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO₂ and Powder models and offers solutions for almost all situations. The internationally-recognised BS Kitemark is assurance of dependable design and manufacture.



COMMANDEREDGE

PRODUCT CODE

FS2E | FS6E | FS6ECO | FS9E

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FS2E: 380 x 125 x 120

FS6E: 502 x 197 x 160

FS6ECO: 550 x 310 x 165

FS9E: 620 x 330 x 185

WEIGHT

FS2E: 4.5kg

FS6E: 9.9kg

FS6ECO: 9.6kg

FS9E: 14.2kg

- Kitemarked to BS EN3
- Manufactured in Europe*
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Plastic base skirt for protection
- Polyethylene internal lining
- 35kVa Dielectric test certified on 6 and 9ltr

*FS6E model only

FOAM FIRE EXTINGUISHERS

Foam is always an excellent choice for Class A and B fires. The standard 6 and 9 litre models have passed the 35kVa Dielectric test and comply fully with BS EN3-7: 2004 Clause 9 - Dielectric test for water-based extinguishers. The newly-developed 6 litre EnviroFoam is a true market leader with an environmentally-friendly foam and boasting a high performance 27A 183B fire rating.

Technical Specification	FS2E	FS6E	FS6ECO	FS9E
Capacity	2 litre	6 litre	6 litre	9 litre
Fire Rating	5A 34B	21A 183B	27A 183B	21A 183B
Extinguishing Medium	AFF Foam	AFF Foam	AFF Foam	AFF Foam
Working Pressure	14 bar	15 bar at temp 20°C	14 bar	14 bar
Temperature Range	+5°-+60°C	+5°-+60°C	+5°-+60°C	+5°-+60°C
Cylinder Material	Steel	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen



029 2086 8333



029 2085 0627



sales@checkfire.co.uk



www.CheckFire.co.uk



MPA
Dresden